The Leading Spot Player for 20 years



NOW WITH FLASH MEMORY!





- Record or Play Directly from SD memory cards
- Store 10,000 Audio Clips to Hard Disk & SD Cards
- Share Files between DigiCart® SD's
- 24-bit Stereo WAV Files
- On-Board Trimming & Playlisting
- Serial Control by Station Automation



KEY FEATURES

Number of audio clips	10,000 per directory
Memory Card	SD Card, SDHC Class 10,
	2GB to 64GB
Internal Hard Disk	160 GB
Delay from Play Command	Instantaneous
Cue to Next Cut	Instantaneous on all drives
Display	Backlit LCD, 7 x 40 characters
Level Metering	Quasi-peak responding
	LED display
Editing Features	Head trim, Tail trim
GPI Remote controls	Remote contacts with
	return lamp drive
Serial Remote control	Full machine control with
	9-pin ES-Bus DigiCart®
Rack Mount Form Factor	2U x 19" rack width

AUDIO Sampling Frequencies 96 kHz. 88.2 kHz. 48 kHz. 44.1 kHz Audio Coding 24 or 16-bit Linear PCM Audio Sync References Internal crystal, AES-3 receiver, AES-11 sync Input Impedance 20K ohms Analog Input Balanced, XLR-3 Analog Output Balanced, XLR-3 Sample Rate Conversion 24-bit, input or output, ratio = 3:1 maximum **Data Reduction** Optional, Dolby AC 2 at 16-bit, 48K only **File Formats** .WAV (16 or 24-bit); .DC2 (16 bit); Dolby® AC2 Headphones Stereo, ¼" front panel jack Signal-to-Noise 115 dB typical Distortion, (THD+N) .0015% full scale Bandwidth, 44.1K or 48K 10Hz - 21 kHz ±0.2 dB Bandwidth, 88.2K or 96K 10 Hz - 42 kHz ±0.2 dB Nominal Operating Level +4 dBu Crosstalk < -100 dB 10 Hz – 20 kHz Dimensions 3.48" (2U) x 19" x 12" (H-W-D)

36 Systems

Tel +1 (818) 991-0360 www.360Systems.com Made in U.S.A.